



Home Theater 3D Projector

## VPL-VW95ES

Bring a beautiful cinema-like experience to your high-end home theater or living room with a bright, vibrant picture, a 150,000:1 dynamic contrast ratio and whisper-quiet operation. New SXR<sup>D</sup> panel technology, optional 2D to 3D converting, and control system compatibility round out the impressive and flexible feature set.

### INSTALLATION FEATURES

Manual zoom/horizontal and vertical focus and shift

1.6x zoom

Shift range: V: +/- 0.65V, H: +/- 0.25H

Whisper-quiet fan: 20dB

Zone panel alignment: 144 zones,  $\frac{1}{10}$  pixel step, panel alignment ensures a sharp image

Recommended for screen sizes up to 150" for 2D and 120" for 3D

Integrated IR 3D sync transmitter

### VIDEO CALIBRATION FEATURES

Powerful, independent 2D and 3D calibration

Nine picture modes, nine gamma adjustments



## SPECS

### 3D Features

- Active 3D ready<sup>1</sup>—supports frame packing, side-by-side, and over-under formats
- Dynamic lamp control for excellent 3D brightness
- 240Hz for reduced crosstalk
- 2D to 3D upconversion<sup>2</sup>
- Supports Sony's new, lighter, rechargeable glasses with integrated polarizing filter (sold separately)
- 3D glasses brightness adjustment
- 3D effect adjustment
- Includes two pairs of rechargeable Sony 3D glasses optimized for front projection, TDG-PJ1

### Video Features

- 150,000:1 dynamic contrast
- Brightness of 1,000 ANSI lumens
- Full HD 1080p with 3 NEW silicon X-tal reflective display SXRD™ 1920x1080 panels
- 240Hz panel drive
- Motionflow™ technology with Dark Frame insertion
- Advanced Auto Iris 3
- Supports Deep Color and x.v.Color™
- All-range crisp focus (ARC-F) lens
- Noise reduction—mosquito and block
- 24p True Cinema Inputs/Outputs

- Lens cover opens and closes automatically when projector powers on and off
- Elevated Standard “ES” brand/support
- Picture position feature for lens-less anamorphic (2.35:1) viewing

### Inputs and Outputs

- Two HDMI® inputs, various analog inputs
- RJ45 jack for optional 3D IR transmitter Integration
- IR Input

### Control Features

- Bi-directional RS232 control
- Control4® Certified/AMX Device Discovery Beacon/Crestron Integration Partner

### Dimensions

- 3-year warranty, including special tech support hotline
- Weight 26.5 lbs
- 18 1/2"(W) x 7 1/16"(H) x 19 1/16"(D)



1. Requires 3D content, 3D player, 3D transmitter, and HDMI® cable (at least 10.2 Gbps).

2. Simulated 3D image will vary based on source content.